

**Techcote™**

Techcote™ is Central Wire's proprietary, non-metallic, soap lubricant coating that enhances consistency and easy removal. Techcote™ is available on wires this a diameter range of 0.022" to .0625".

**TechBrite™**

A Techbrite™ finish imparts a mirror like finish on bare bright drawn wire. It's This specialty spring wire coating is recommended for applications that require a bright, lustrous appearance. A Techbrite™ finish is available on spring wires with diameters of 0.020" to 0.125".

**Nickel Flash Coatings**

Nickel Coatings offer improved lubricity and greater corrosion resistance for spring wire applications. Available on select alloys and sizes. Call to discuss application and availability.

**Copper With Soap**

Copper with Soap spring wire coating is available on wires that are drawn with Techcote™ and with diameters from .020" to 0.625".

Alloy	Available Size Range (inches)		
	Techcote™	TechBrite™	Nickel Flash*
302/304	0.023 – 0.625	0.003 – 0.125	0.023 – 0.625
316/316L	0.023 – 0.625	0.003 – 0.125	0.023 – 0.625
17-7 PH	0.023 – 0.625	0.003 – 0.125	0.023 – 0.625
Inconel 600	0.003 – 0.625	0.003 – 0.125	0.003 – 0.625
Inconel 625	0.003 – 0.625	0.003 – 0.125	0.003 – 0.625
Inconel 718	0.003 – 0.625	0.003 – 0.125	0.003 – 0.625
X750	0.003 – 0.625	0.003 – 0.125	0.003 – 0.625
Monel 400	0.003 – 0.625	0.003 – 0.125	0.003 – 0.625
K-500	0.003 – 0.625	0.003 – 0.125	0.003 – 0.625
Hastelloy C276	0.003 – 0.625	0.003 – 0.125	0.003 – 0.625
MP35N	0.003 – 0.625	0.003 – 0.125	0.003 – 0.625
Nitronic 50	0.003 – 0.625	0.003 – 0.125	0.003 – 0.625